
SMD Crystal Oscillators

D2SX Series 2.5×2.0×0.9mm



Features
- Very small SMD package
- Low power standby mode


Applications
- High quality audio
- Smartphone, Tablet, Notebook
- Server
- Wireless module

Electrical Specifications


Item	Symbol	Condition	D2SX			
Frequency Range	f_{nom}	-	1~125MHz			
Output Type	-	-	CMOS			
Output Load	-	-	15pF, or specify			
Frequency Stability*	f_{stb}	All Condition*	±25ppm, or specify			
Operating Temperature Range	T_{opr}	-	-20~+70℃, or specify			
Storage Temperature Range	T_{stg}	-	-40~+85℃			
Power Supply Voltage	V_{DD}	-	3.3V±10%	2.8V±10%	1.8V±10%	1.2V±10%
Supply Current (At 15pF Load)	I_{DD}	1.0~19.9MHz	5mA max.	4mA max.	3mA max.	2mA max.
		20.0~49.9MHz	8mA max.	7mA max.	5mA max.	3mA max.
		50.0~69.9MHz	12mA max.	10mA max.	8mA max.	-
		70.0~125.0MHz	30mA max.	25mA max.	20mA max.	-
Rise Time / Fall Time	T_r/T_f	10%V_{DD}~90%V_{DD}	4ns max.	5ns max.	6ns max.	10ns max.
Output Voltage	V_{OH}	-	90%V_{DD} min.			
	V_{OL}	-	10%V_{DD} max.			
Output Symmetry	SYM	At 1/2 V_{DD}	45%~55%			
Stand-by Current	Ist	-	10μA max.			
Start-up time	-	-	5ms max.			
Aging (At 25℃)	-	-	±3 ppm/year max.			
Pin 1, Enable/Disable function	E/D	-	Pin 1="High" or "open".....output active at pin 3 Pin 1="Low".....high impedance at pin 3			

* Include : 25℃ tolerance, operating temperature range, input voltage change, aging, load change.

Mechanical Dimensions



Output Waveform



** 0.01uF bypass capacitor should be placed between V_{DD} (pin 4) and GND (pin 2) to minimize power supply line noise.

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

微信扫码咨询客服