

SG2525A
SG3525A

REGULATING PULSE WIDTH MODULATORS

- 8 TO 35 V OPERATION
- 5.1 V REFERENCE TRIMMED TO ± 1 %
- 100 Hz TO 500 KHz OSCILLATOR RANGE
- SEPARATE OSCILLATOR SYNC TERMINAL
- ADJUSTABLE DEADTIME CONTROL
- INTERNAL SOFT-START
- PULSE-BY-PULSE SHUTDOWN
- INPUT UNDERVOLTAGE LOCKOUT WITH HYSTERESIS
- LATCHING PWM TO PREVENT MULTIPLE PULSES
- DUAL SOURCE/SINK OUTPUT DRIVERS



DIP16




16(Narrow)

DESCRIPTION

The SG3525A series of pulse width modulator integrated circuits are designed to offer improved performance and lowered external parts count when used in designing all types of switching power supplies. The on-chip + 5.1 V reference is trimmed to ± 1 % and the input common-mode range of the error amplifier includes the reference voltage eliminating external resistors. A sync input to the oscillator allows multiple units to be slaved or a single unit to be synchronized to an external system clock. A single resistor between the C_T and the discharge terminals provide a wide range of dead time ad- justment. These devices also feature built-in soft-start circuitry with only an external timing capacitor required. A shutdown terminal controls both the soft-start circuity and the output stages, providing instantaneous turn off through the PWM latch with pulsed shutdown, as well as soft-start recycle with longer shutdown commands. These functions are also controlled by an undervoltage lockout which keeps the outputs off and the soft-start capacitor discharged for sub-normal input voltages. This lockout circuitry includes approximately 500 mV of hysteresis for jitter-free operation. Another feature of these PWM circuits is a latch following the comparator. Once a PWM pulses has been terminated for any reason, the outputs will remain off for the duration of the period. The latch is reset with each clock pulse. The output stages are totem-pole designs capable of sourcing or sinking in excess of 200 mA. The SG3525A output stage features NOR logic, giving a LOW output for an OFF state.

PIN CONNECTIONS AND ORDERING NUMBERS (top view)



Type	Plastic DIP	SO16
SG2525A	SG2525AN	SG2525AP
SG3525A	SG3525AN	SG3525AP

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com
微信扫码咨询客服

ABSOLUTE MAXIMUM RATINGS


Symbol	Parameter	Value	Unit
V_i	Supply Voltage	40	V
V_C	Collector Supply Voltage	40	V
I_{OSC}	Oscillator Charging Current	5	mA
I_o	Output Current, Source or Sink	500	mA
I_R	Reference Output Current	50	mA
I_T	Current through C_T Terminal Logic Inputs Analog Inputs	5 – 0.3 to + 5.5 – 0.3 to V_i	mA V V
P_{tot}	Total Power Dissipation at T_{amb} = 70 °C	1000	mW
T_j	Junction Temperature Range	– 55 to 150	°C
T_{stg}	Storage Temperature Range	– 65 to 150	°C
T_{op}	Operating Ambient Temperature : **SG2525A** **SG3525A**	– 25 to 85 0 to 70	°C °C

THERMAL DATA

Symbol	Parameter		SO16	DIP16	Unit
$R_{th\ j\text{-}pins}$	Thermal Resistance Junction-pins	Max		50	°C/W
$R_{th\ j\text{-}amb}$	Thermal Resistance Junction-ambient	Max		80	°C/W
$R_{th\ j\text{-}alumina}$	Thermal Resistance Junction-alumina (*)	Max	50		°C/W

* Thermal resistance junction-alumina with the device soldered on the middle of an alumina supporting substrate measuring 15 × 20 mm ; 0.65 mm thickness with infinite heatsink.

BLOCK DIAGRAM



深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

ELECTRICAL CHARACTERISTICS

(V# i = 20 V, and over operating temperature, unless otherwise specified)

Symbol	Parameter	Test Conditions	SG2525A			SG3525A			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	
REFERENCE SECTION									
V_{REF}	Output Voltage	T_j = 25 °C	5.05	5.1	5.15	5	5.1	5.2	V
ΔV_{REF}	Line Regulation	V_i = 8 to 35 V		10	20		10	20	mV
ΔV_{REF}	Load Regulation	I_L = 0 to 20 mA		20	50		20	50	mV
$\Delta V_{REF}/\Delta T$*	Temp. Stability	Over Operating Range		20	50		20	50	mV
*	Total Output Variation	Line, Load and Temperature	5		5.2	4.95		5.25	V
	Short Circuit Current	V_{REF} = 0 T_j = 25 °C		80	100		80	100	mA
*	Output Noise Voltage	10 Hz ≤f ≤ 10 kHz, T_j = 25 °C		40	200		40	200	μVrms
ΔV_{REF}*	Long Term Stability	T_j = 125 °C, 1000 hrs		20	50		20	50	mV
OSCILLATOR SECTION * *									
*, •	Initial Accuracy	T_j = 25 °C		± 2	± 6		± 2	± 6	%
*, •	Voltage Stability	V_i = 8 to 35 V		± 0.3	± 1		± 1	± 2	%
$\Delta f/\Delta T$*	Temperature Stability	Over Operating Range		± 3	± 6		± 3	± 6	%
f_{MIN}	Minimum Frequency	R_T = 200 KΩ C_T = 0.1 μF			120			120	Hz
f_{MAX}	Maximum Frequency	R_T = 2 KΩ C_T = 470 pF	400			400			KHz
	Current Mirror	I_{RT} = 2 mA	1.7	2	2.2	1.7	2	2.2	mA
*, •	Clock Amplitude		3	3.5		3	3.5		V
*, •	Clock Width	T_j = 25 °C	0.3	0.5	1	0.3	0.5	1	μs
	Sync Threshold		1.2	2	2.8	1.2	2	2.8	V
	Sync Input Current	Sync Voltage = 3.5 V		1	2.5		1	2.5	mA
ERROR AMPLIFIER SECTION (V_{CM} = 5.1 V)									
V_{OS}	Input Offset Voltage			0.5	5		2	10	mV
I_b	Input Bias Current			1	10		1	10	μA
I_{os}	Input Offset Current				1			1	μA
	DC Open Loop Gain	R_L ≥ 10 MΩ	60	75		60	75		dB
*	Gain Bandwidth Product	G_v = 0 dB T_j = 25 °C	1	2		1	2		MHz
*, ∎	DC Transconduct.	30 KΩ ≤ R_L ≤ 1 MΩ T_j = 25 °C	1.1	1.5		1.1	1.5		ms
	Output Low Level			0.2	0.5		0.2	0.5	V
	Output High Level		3.8	5.6		3.8	5.6		V
CMR	Comm. Mode Reject.	V_{CM} = 1.5 to 5.2 V	60	75		60	75		dB
PSR	Supply Voltage Rejection	V_i = 8 to 35 V	50	60		50	60		dB

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

ELECTRICAL CHARACTERISTICS (continued)

Symbol	Parameter	Test Conditions	SG2525A			SG3525A			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	
PWM COMPARATOR									
	Minimum Duty-cycle				0			0	%
•	Maximum Duty-cycle		45	49		45	49		%
•	Input Threshold	Zero Duty-cycle	0.7	0.9		0.7	0.9		V
		Maximum Duty-cycle		3.3	3.6		3.3	3.6	V
*	Input Bias Current			0.05	1		0.05	1	µA
SHUTDOWN SECTION									
	Soft Start Current	V_{SD} = 0 V, V_{SS} = 0 V	25	50	80	25	50	80	µA
	Soft Start Low Level	V_{SD} = 2.5 V		0.4	0.7		0.4	0.7	V
	Shutdown Threshold	To outputs, V_{SS} = 5.1 V T_j = 25 °C	0.6	0.8	1	0.6	0.8	1	V
	Shutdown Input Current	V_{SD} = 2.5 V		0.4	1		0.4	1	mA
*	Shutdown Delay	V_{SD} = 2.5 V T_j = 25 °C		0.2	0.5		0.2	0.5	µs
OUTPUT DRIVERS (each output) (V_C = 20 V)									
	Output Low Level	I_{sink} = 20 mA		0.2	0.4		0.2	0.4	V
		I_{sink} = 100 mA		1	2		1	2	V
	Output High Level	I_{source} = 20 mA	18	19		18	19		V
		I_{source} = 100 mA	17	18		17	18		V
	Under-Voltage Lockout	V_{comp} and V_{ss} = High	6	7	8	6	7	8	V
I_C	Collector Leakage	V_C = 35 V			200			200	µA
t_r*	Rise Time	C_L = 1 nF, T_j = 25 °C		100	600		100	600	ns
t_f*	Fall Time	C_L = 1 nF, T_j = 25 °C		50	300		50	300	ns
TOTAL STANDBY CURRENT									
I_s	Supply Current	V_i = 35 V		14	20		14	20	mA

* These parameters, although guaranteed over the recommended operating conditions, are not 100 % tested in production.


• Tested at f_{osc} = 40 KHz (R_T = 3.6 KΩ, C_T = 10nF, R_D = 0 Ω). Approximate oscillator frequency is defined by :

$$f = \frac{1}{C_T(0.7\,R_T + 3\,R_D)}$$

■ DC transconductance (g_M) relates to DC open-loop voltage gain (G_v) according to the following equation : $G_v = g_M\,R_L$ where R_L is the resistance from pin 9 to ground. The minimum g_M specification is used to calculate minimum G_v when the error amplifier output is loaded.

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

TEST CIRCUIT



深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

RECOMMENDED OPERATING CONDITIONS (•)

Parameter	Value
Input Voltage (V_i)	8 to 35 V
Collector Supply Voltage (V_C)	4.5 to 35 V
Sink/Source Load Current (steady state)	0 to 100 mA
Sink/Source Load Current (peak)	0 to 400 mA
Reference Load Current	0 to 20 mA
Oscillator Frequency Range	100 Hz to 400 KHz
Oscillator Timing Resistor	2 KΩ to 150 KΩ
Oscillator Timing Capacitor	0.001 µF to 0.1 µF
Dead Time Resistor Range	0 to 500 Ω

(•) Range over which the device is functional and parameter limits are guaranteed.

Figure 1 : Oscillator Charge Time vs. R_T and C_T.




Figure 2 : Oscillator Discharge Time vs. R_D and C_T.




Figure 3 : Output Saturation Characteristics.






Figure 4 : Error Amplifier Voltage Gain and Phase vs. Frequency.



深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

Figure 5 : Error Amplifier.



PRINCIPLES OF OPERATION

SHUTDOWN OPTIONS (see Block Diagram)

Since both the compensation and soft-start terminals (Pins 9 and 8) have current source pull-ups, either can readily accept a pull-down signal which only has to sink a maximum of 100 µA to turn off the outputs. This is subject to the added requirement of discharging whatever external capacitance may be attached to these pins.

An alternate approach is the use of the shutdown circuitry of Pin 10 which has been improved to enhance the available shutdown options. Activating this circuit by applying a positive signal on Pin 10 performs two functions : the PWM latch is immediately set providing the fastest turn-off signal to the outputs ; and a 150 µA current sink begins to discharge the external soft-start capacitor. If the shutdown command is short, the PWM signal is terminated without significant discharge of the soft-start capacitor, thus, allowing, for example, a convenient implementation of pulse-by-pulse current limiting. Holding Pin 10 high for a longer duration, however, will ultimately discharge this external capacitor, recycling slow turn-on upon release.

Pin 10 should not be left floating as noise pickup could conceivably interrupt normal operation.

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

Figure 6 : Oscillator Schematic.






Figure 7 : Output Circuit (1/2 circuit shown).




深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

Figure 8.




For single-ended supplies, the driver outputs are grounded. The V_C terminal is switched to ground by the totem-pole source transistors on alternate oscillator cycles.

Figure 9.




In conventional push-pull bipolar designs, forward base drive is controlled by R_1 - R_3. Rapid turn-off times for the power devices are achieved with speed-up capacitors C_1 and C_2.

Figure 10.



The low source impedance of the output drivers provides rapid charging of Power Mos input capacitance while minimizing external components.

Figure 11.




Low power transformers can be driven directly. Automatic reset occurs during dead time, when both ends of the primary winding are switched to ground.


深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
a1	0.51			0.020		
B	0.77		1.65	0.030		0.065
b		0.5			0.020	
b1		0.25			0.010	
D			20			0.787
E		8.5			0.335	
e		2.54			0.100	
e3		17.78			0.700	
F			7.1			0.280
I			5.1			0.201
L		3.3			0.130	
Z			1.27			0.050

OUTLINE AND MECHANICAL DATA




DIP16



深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com


DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A			1.75			0.069
a1	0.1		0.25	0.004		0.009
a2			1.6			0.063
b	0.35		0.46	0.014		0.018
b1	0.19		0.25	0.007		0.010
C		0.5			0.020	
c1	45˚ (typ.)					
D (1)	9.8		10	0.386		0.394
E	5.8		6.2	0.228		0.244
e		1.27			0.050	
e3		8.89			0.350	
F (1)	3.8		4	0.150		0.157
G	4.6		5.3	0.181		0.209
L	0.4		1.27	0.016		0.050
M			0.62			0.024
S	8˚(max.)					

OUTLINE AND MECHANICAL DATA



SO16 Narrow

(1) D and F do not include mold flash or protrusions. Mold flash or potrusions shall not exceed 0.15mm (.006inch).



深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2000 STMicroelectronics – Printed in Italy – All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

http://www.st.com

深圳市满度科技有限公司
Web:www.manduic.com

Tel:150-1290-5940
Email:sales@manduic.com