W29N01HZ/WxxNF
1G-BIT 1.8V
NAND FLASH MEMORY

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com
微信扫码咨询客服

winbond

Table of Contents

1. GENERAL DESCRIPTION 6
2. FEATURES 6
3. PACKAGE TYPES AND PIN CONFIGURATIONS 7
   - 3.1 Pin Assignment 48 pin TSOP1 (x8) 7
   - 3.2 Pin Assignment 48 ball VFBGA (x8) 8
   - 3.3 Pin Assignment 48 ball VFBGA (x16) 9
   - 3.4 Pin Assignment 63 ball VFBGA (x8) 10
   - 3.5 Pin Assignment 63 ball VFBGA (x16) 11
   - 3.6 Pin Descriptions 12
4. PIN DESCRITPIONS 13
   - 4.1 Chip Enable (#CE) 13
   - 4.2 Write Enable (#WE) 13
   - 4.3 Read Enable (#RE) 13
   - 4.4 Address Latch Enable (ALE) 13
   - 4.5 Command Latch Enable (CLE) 13
   - 4.6 Write Protect (#WP) 13
   - 4.7 Ready/Busy (RY/#BY) 13
   - 4.8 Input and Output (I/Ox) 13
5. BLOCK DIAGRAM 14
6. MEMORY ARRAY ORGANIZATION 15
   - 6.1 Array Organization (x8) 15
   - 6.2 Array Organization (x16) 16
7. MODE SELECTION TABLE 17
8. COMMAND TABLE 18
9. DEVICE OPERATIONS 19
   - 9.1 READ Operation 19
     - 9.1.1 PAGE READ (00h-30h) 19
     - 9.1.2 RANDOM DATA OUTPUT (05h-E0h) 20
     - 9.1.3 READ ID (90h) 20
     - 9.1.4 READ PARAMETER PAGE (ECh) 21
     - 9.1.5 READ STATUS (70h) 24
   - 9.2 PROGRAM Operation 25
     - 9.2.1 PAGE PROGRAM (80h-10h) 25
     - 9.2.2 SERIAL DATA INPUT (80h) 25
     - 9.2.3 RANDOM DATA INPUT (85h) 26
   - 9.3 COPY BACK Operation 27
     - 9.3.1 READ for COPY BACK (00h-35h) 27
     - 9.3.2 PROGRAM for COPY BACK (85h-10h) 27
   - 9.4 BLOCK ERASE Operation 29
     - 9.4.1 BLOCK ERASE (60h-D0h) 29
   - 9.5 RESET Operation 30
     - 9.5.1 RESET (FFh) 30
   - 9.6 WRITE PROTECT 31

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

10. ELECTRICAL CHARACTERISTICS 33
10.1 Absolute Maximum Ratings (1.8V) 33
10.2 Operating Ranges (1.8V) 33
10.3 Device Power-up Timing 34
10.4 DC Electrical Characteristics 35
10.6 AC Measurement Conditions 36
10.7 AC Timing Characteristics for Command, Address and Data Input (1.8V) 37
10.8 AC Timing Characteristics for Operation (1.8V) 38
10.9 Program and Erase Characteristics 39
11. TIMING DIAGRAMS 40
12. INVALID BLOCK MANAGEMENT 49
12.1 Invalid Blocks 49
12.2 Initial Invalid Blocks 49
12.3 Error in Operation 51
12.4 Addressing in Program Operation 51
13. PACKAGE DIMENSIONS 52
13.1 TSOP 48-pin 12x20 52
13.2 Fine-Pitch Ball Grid Array 48-ball 53
13.3 Fine-Pitch Ball Grid Array 63-ball 54
14. ORDERING INFORMATION 55
15. VALID PART NUMBERS 56
16. REVISION HISTORY 58

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

List of Tables

Table 3.1 Pin Descriptions 12
Table 6.1 Addressing 15
Table 6.2 Addressing 16
Table 7.1 Mode Selection 17
Table 8.1 Command Table 18
Table 9.1 Device ID and configuration codes for Address 00h 21
Table 9.2 ONFI identifying codes for Address 20h 21
Table 9.3 Parameter Page Output Value 23
Table 9.4 Status Register Bit Definition 24
Table 10.1 Absolute Maximum Ratings 33
Table 10.2 Operating Ranges 33
Table 10.3 DC Electrical Characteristics 35
Table 10.4 AC Measurement Conditions 36
Table 10.5 AC Timing Characteristics for Command, Address and Data Input 37
Table 10.6 AC Timing Characteristics for Operation 38
Table 10.7 Program and Erase Characteristics 39
Table 12.1 Valid Block Number 49
Table 12.2 Block Failure 51
Table 15.1 Part Numbers for Industrial Temperature 56
Table 15.2 Part Numbers for Industrial Plus Temperature 57
Table 16.1 History Table 58

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

List of Figures

Figure 3-1 Pin Assignment 48-pin TSOP1 (Package code S) 7
Figure 3-2 Pin Assignment 48-ball VFBGA (Package code D) 8
Figure 3-3 Pin Assignment 48-ball VFBGA (Package code D) 9
Figure 3-4 Pin Assignment 63-ball VFBGA (Package Code B) 10
Figure 3-5 Pin Assignment 63-ball VFBGA (Package Code B) 11
Figure 5-1 NAND Flash Memory Block Diagram 14
Figure 6-1 Array Organization 15
Figure 6-2 Array Organization 16
Figure 9-1 Page Read Operations 19
Figure 9-2 Random Data Output 20
Figure 9-3 Read ID 20
Figure 9-4 Read Parameter Page 21
Figure 9-5 Read Status Operation 24
Figure 9-6 Page Program 25
Figure 9-7 Random Data Input 26
Figure 9-8 Copy Back Program Operation 28
Figure 10-1 Power ON/OFF sequence 34
Figure 11-1 Command Latch Cycle 40
Figure 11-2 Address Latch Cycle 40
Figure 11-3 Data Latch Cycle 41
Figure 11-4 Serial Access Cycle after Read 41
Figure 11-5 Serial Access Cycle after Read (EDO) 42
Figure 11-6 Read Status Operation 42
Figure 11-7 Page Read Operation 43
Figure 11-8 #CE Don't Care Read Operation 43
Figure 11-9 Random Data Output Operation 44
Figure 11-10 Read ID 45
Figure 11-11 Page Program 45
Figure 11-12 #CE Don't Care Page Program Operation 46
Figure 11-13 Page Program with Random Data Input 46
Figure 11-14 Copy Back 47
Figure 11-15 Block Erase 47
Figure 11-16 Reset 48
Figure 12-1 Flow Chart of Create Initial Invalid Block Table 50
Figure 12-2 Bad Block Replacement 51
Figure 14-1 Ordering Part Number Description 55

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

1. GENERAL DESCRIPTION

The W29N01HZ/W (1G-bit) NAND Flash memory provides a storage solution for embedded systems with limited space, pins and power. It is ideal for code shadowing to RAM, solid state applications and storing media data such as, voice, video, text and photos. The device operates on a single 1.7V to 1.95V power supply with active current consumption as low as 13mA at 1.8V and 10uA for CMOS standby current.

The memory array totals 138,412,032 bytes, and organized into 1,024 erasable blocks of 135,168 bytes (135,168 words). Each block consists of 64 programmable pages of 2,112-bytes (1056 words) each. Each page consists of 2,048-bytes (1024 words) for the main data storage area and 64-bytes (32words) for the spare data area (The spare area is typically used for error management functions).

The W29N01HZ/W supports the standard NAND flash memory interface using the multiplexed 8-bit (16-bit) bus to transfer data, addresses, and command instructions. The five control signals, CLE, ALE, #CE, #RE and #WE handle the bus interface protocol. Also, the device has two other signal pins, the #WP (Write Protect) and the RY/#BY (Ready/Busy) for monitoring the device status.

2. FEATURES

- **Basic Features**
  - – Density : 1Gbit (Single chip solution)
  - – Vcc : 1.7V to 1.95V
  - – Bus width : x8 x16
  - – Operating temperature
    - ▪ Industrial: -40°C to 85°C
    - ▪ Industrial Plus: -40°C to 105°C
- **Single-Level Cell (SLC) technology.**
- **Organization**
  - – Density: 1G-bit/128M-byte
  - – Page size
    - ▪ 2,112 bytes (2048 + 64 bytes)
    - ▪ 1,056 words (1024 + 32 words)
  - – Block size
    - ▪ 64 pages (128K + 4K bytes)
    - ▪ 64 pages (64K + 2K words)
- **Highest Performance**
  - – Read performance (Max.)
    - ▪ Random read: 25us
    - ▪ Sequential read cycle: 25ns
  - – Write Erase performance
    - ▪ Page program time: 250us(typ.)
    - ▪ Block erase time: 2ms(typ.)
  - – Endurance 100,000 Erase/Program Cycles(1)
  - – 10-years data retention
- **Command set**
  - – Standard NAND command set
  - – Additional command support
    - ▪ Copy Back
- **Lowest power consumption**
  - – Read: 13mA(typ.)
  - – Program/Erase: 10mA(typ.)
  - – CMOS standby: 10uA(typ.)
- **Space Efficient Packaging**
  - – 48-pin standard TSOP1
  - – 48-ball VFBGA
  - – 63-ball VFBGA
  - – Contact Winbond for stacked packages/KGD

Note:

1. **Endurance specification is based on 4bit/528 byte ECC (Error Correcting Code).**

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

3. PACKAGE TYPES AND PIN CONFIGURATIONS

W29N01HZ/W is offered in a 48-pin TSOP1 package (Code S), 48-ball (Code D) and 63-ball (Code B) VFBGA package as shown in Figure 3-1 to 3-5, respectively. Package diagrams and dimensions are illustrated in Section: Package Dimensions.

3.1 Pin Assignment 48 pin TSOP1 (x8)




Figure 3-1 Pin Assignment 48-pin TSOP1 (Package code S)

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

3.2 Pin Assignment 48 ball VFBGA (x8)

Top View, ball down




Figure 3-2 Pin Assignment 48-ball VFBGA (Package code D)

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

3.3 Pin Assignment 48 ball VFBGA (x16)

Top View, ball down




Figure 3-3 Pin Assignment 48-ball VFBGA (Package code D)

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

3.4 Pin Assignment 63 ball VFBGA (x8)




Figure 3-4 Pin Assignment 63-ball VFBGA (Package Code B)

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

3.5 Pin Assignment 63 ball VFBGA (x16)




Figure 3-5 Pin Assignment 63-ball VFBGA (Package Code B)

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

3.6 Pin Descriptions

PIN NAME	I/O	FUNCTION
#WP	I	Write Protect
ALE	I	Address Latch Enable
#CE	I	Chip Enable
#WE	I	Write Enable
RY/#BY	O	Ready/Busy
#RE	I	Read Enable
CLE	I	Command Latch Enable
I/O[0-7] I/O[0-15]	I/O	Data Input/Output (x8,x16)
Vcc	Supply	Power supply
Vss	Supply	Ground
DNU	-	Do Not Use: DNUs must be left unconnected.
N.C	-	No Connect

Table 3.1 Pin Descriptions

Note:

1. **Connect all Vcc and Vss pins to power supply or ground. Do not leave Vcc or Vss disconnected.**

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

4. PIN DESCRITPIONS

4.1 Chip Enable (#CE)

#CE pin enables and disables device operation. When #CE is high the device is disabled and the I/O pins are set to high impedance and enters into standby mode if not busy. When #CE is set low the device will be enabled, power consumption will increase to active levels and the device is ready for Read and Write operations.

4.2 Write Enable (#WE)

#WE pin enables the device to control write operations to input pins of the device. Such as, command instructions, addresses and data that are latched on the rising edge of #WE.

4.3 Read Enable (#RE)

#RE pin controls serial data output from the pre-loaded Data Register. Valid data is present on the I/O bus after the tREA period from the falling edge of #RE. Column addresses are incremented for each #RE pulse.

4.4 Address Latch Enable (ALE)

ALE pin controls address input to the address register of the device. When ALE is active high, addresses are latched via the I/O pins on the rising edge of #WE.

4.5 Command Latch Enable (CLE)

CLE pin controls command input to the command register of the device. When CLE is active high, commands are latched into the command register via I/O pins on the rising edge of #WE.

4.6 Write Protect (#WP)

#WP pin can be used to prevent the inadvertent program/erase to the device. When #WP pin is active low, all program/erase operations are disabled.

4.7 Ready/Busy (RY/#BY)

RY/#BY pin indicates the device status. When RY/#BY output is low, it indicates that the device is processing either a program, erase or read operations. When it returns to high, those operations have completed. RY/#BY pin is an open drain.

4.8 Input and Output (I/Ox)

I/Ox bi-directional pins are used for the following; command, address and data operations.

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

5. BLOCK DIAGRAM




Figure 5-1 NAND Flash Memory Block Diagram

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

6. MEMORY ARRAY ORGANIZATION

6.1 Array Organization (x8)




Figure 6-1 Array Organization

	I/O7	I/O6	I/O5	I/O4	I/O3	I/O2	I/O1	I/O0
1st cycle	A7	A6	A5	A4	A3	A2	A1	A0
2nd cycle	L	L	L	L	A11	A10	A9	A8
3rd cycle	A19	A18	A17	A16	A15	A14	A13	A12
4th cycle	A27	A26	A25	A24	A23	A22	A21	A20

Table 6.1 Addressing

Notes:

1. **"L" indicates a low condition, which must be held during the address cycle to insure correct processing.**
2. **A0 to A11 during the 1st and 2nd cycles are column addresses. A12 to A27 during the 3rd and 4th cycles are row addresses.**
3. **The device ignores any additional address inputs that exceed the device's requirement.**

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

6.2 Array Organization (x16)




Figure 6-2 Array Organization

	I/O8~15	I/O7	I/O6	I/O5	I/O4	I/O3	I/O2	I/O1	I/O0
1st cycle	L	A7	A6	A5	A4	A3	A2	A1	A0
2nd cycle	L	L	L	L	L	L	A10	A9	A8
3rd cycle	L	A18	A17	A16	A15	A14	A13	A12	A11
4th cycle	L	A26	A25	A24	A23	A22	A21	A20	A19

Table 6.2 Addressing

Notes:

*** "L" must to be held Low during the address cycle is inputted**

*** A0 to A10 of 1st and 2nd cycle are column address, A11 to A26 of 3rd and 4th cycle are row address**

*** The device ignores any additional address input than the device is required**

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

7. MODE SELECTION TABLE

MODE		CLE	ALE	#CE	#WE	#RE	#WP
Read mode	Command input	H	L	L		H	X
	Address input	L	H	L		H	X
Program Erase mode	Command input	H	L	L		H	H
	Address input	L	H	L		H	H
Data input		L	L	L		H	H
Sequential Read and Data output		L	L	L	H		X
During read (busy)		X	X	X	X	H	X
During program (busy)		X	X	X	X	X	H
During erase (busy)		X	X	X	X	X	H
Write protect		X	X	X	X	X	L
Standby		X	X	H	X	X	0V/Vcc

Table 7.1 Mode Selection

Notes:

1. **"H" indicates a HIGH input level, "L" indicates a LOW input level, and "X" indicates a Don't Care Level.**
2. **#WP should be biased to CMOS HIGH or LOW for standby.**

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

8. COMMAND TABLE

COMMAND	1ST CYCLE	2ND CYCLE	3rd CYCLE	4th CYCLE	Acceptable during busy
PAGE READ	00h	30h			
READ for COPY BACK	00h	35h			
READ ID	90h				
READ STATUS	70h				Yes
RESET	FFh				Yes
PAGE PROGRAM	80h	10h			
PROGRAM for COPY BACK	85h	10h			
BLOCK ERASE	60h	D0h			
RANDOM DATA INPUT*1	85h				
RANDOM DATA OUTPUT*1	05h	E0h			
READ PARAMETER PAGE	ECh				

Table 8.1 Command Table

Notes:

1. **RANDOM DATA INPUT and RANDOM DATA OUTPUT command is only to be used within a page.**
2. **Any command that are not in the above table are considered as undefined and are prohibited as inputs.**

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

9. DEVICE OPERATIONS

9.1 READ Operation

9.1.1 PAGE READ (00h-30h)

When the device powers on, 00h command is latched to command register. Therefore, system only issues four address cycles and 30h command for initial read from the device. This operation can also be entered by writing 00h command to the command register, and then write four address cycles, followed by writing 30h command. After writing 30h command, the data is transferred from NAND array to Data Register during tR. Data transfer progress can be done by monitoring the status of the RY/#BY signal output. RY/#BY signal will be LOW during data transfer. Also, there is an alternate method by using the READ STATUS (70h) command. If the READ STATUS command is issued during read operation, the Read (00h) command must be re-issued to read out the data from Data Register. When the data transfer is complete, RY/#BY signal goes HIGH, and the data can be read from Data Register by toggling #RE. Read is sequential from initial column address to the end of the page. (See Figure 9-1)




Figure 9-1 Page Read Operations

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

9.1.2 RANDOM DATA OUTPUT (05h-E0h)

The RANDOM DATA OUTPUT allows the selection of random column addresses to read out data from a single or multiple of addresses. The use of the RANDOM DATA OUTPUT command is available after the PAGE READ (00h-30h) sequence by writing the 05h command following by the two cycle column address and then the E0h command. Toggling #RE will output data sequentially. The RANDOM DATA OUTPUT command can be issued multiple times, but limited to the current loaded page.




Figure 9-2 Random Data Output

9.1.3 READ ID (90h)

READ ID command is comprised of two modes determined by the input address, device (00h) or ONFI (20h) identification information. To enter the READ ID mode, write 90h to the Command Register followed by a 00h address cycle, then toggle #RE for 5 single byte cycles, W29N01HZ/W. The pre-programmed code includes the Manufacturer ID, Device ID, and Product-Specific Information (see Table 9.1). If the READ ID command is followed by 20h address, the output code includes 4 single byte cycles of ONFI identifying information (See Table 9.2). The device remains in the READ ID Mode until the next valid command is issued.




Figure 9-3 Read ID

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

# of Byte/Cycles	1st Byte/Cycle	2nd Byte/Cycle	3rd Byte/Cycle	4th Byte/Cycle	5th Byte/Cycle
W29N01HZ	EFh	A1h	00h	95h	00h
W29N01HW	EFh	B1h	00h	D5h	00h
Description	MFR ID	Device ID	Cache Programming Non-supported	Page Size:2KB Spare Area Size:64B BLK Size w/o Spare:128KB Organized:x8 or x16 Serial Access:25ns	

x16 device : the ID is outputted at word units, and defined lower-byte (IO0-7). ID table shows only lower-byte ID.

Table 9.1 Device ID and configuration codes for Address 00h

# of Byte/Cycles	1st Byte/Cycle	2nd Byte/Cycle	3rd Byte/Cycle	4th Byte/Cycle
Code	4Fh	4Eh	46h	49h

Table 9.2 ONFI Identifying Codes for Address 20h

9.1.4 READ PARAMETER PAGE (ECh)

READ PARAMETER PAGE can read out the device's parameter data structure, such as, manufacturer information, device organization, timing parameters, key features, and other pertinent device parameters. The data structure is stored with at least three copies in the device's parameter page. Figure 9-4 shows the READ PARAMETER PAGE timing. The RANDOM DATA OUTPUT (05h-E0h) command is supported during data output.




Figure 9-4 Read Parameter Page

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

Byte	Description		Value
0-3	Parameter page signature		4Fh, 4Eh, 46h, 49h
4-5	Revision number		02h, 00h
6-7	Features supported	W29N01HZ	10h, 00h
		W29N01HW	11h, 00h
8-9	Optional commands supported		10h, 00h
10-31	Reserved		00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h
32-43	Device manufacturer		57h, 49h, 4Eh, 42h, 4Fh, 4Eh, 44h, 20h, 20h, 20h, 20h, 20h
44-63	Device model	W29N01HZ	57h, 32h, 39h, 4Eh, 30h, 31h, 48h, 5Ah, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h
		W29N01HW	57h, 32h, 39h, 4Eh, 30h, 31h, 48h, 57h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h, 20h
64	Manufacturer ID		EFh
65-66	Date code		00h, 00h
67-79	Reserved		00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h
80-83	# of data bytes per page		00h, 08h, 00h, 00h
84-85	# of spare bytes per page		40h, 00h
86-89	# of data bytes per partial page		00h, 02h, 00h, 00h
90-91	# of spare bytes per partial page		10h, 00h
92-95	# of pages per block		40h, 00h, 00h, 00h
96-99	# of blocks per unit		00h, 04h, 00h, 00h
100	# of logical units		01h
101	# of address cycles		22h
102	# of bits per cell		01h
103-104	Bad blocks maximum per unit		14h, 00h
105-106	Block endurance		01h, 05h
107	Guaranteed valid blocks at beginning of target		01h
108-109	Block endurance for guaranteed valid blocks		00h, 00h
110	# of programs per page		04h
111	Partial programming attributes		00h
112	# of ECC bits		04h

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

Byte	Description		Value
113	# of interleaved address bits		00h
114	Interleaved operation attributes		00h
115-127	Reserved		00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h
128	I/O pin capacitance		0Ah
129-130	Timing mode support	W29N01HZ	07h, 00h
		W29N01HW	07h, 00h
131-132	Program cache timing		00h, 00h
133-134	Maximum page program time		BCh, 02h
135-136	Maximum block erase time		10h, 27h
137-138	Maximum random read time		19h, 00h
139-140			50h, 00h
141-163	Reserved		00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h, 00h
164-165	Vendor specific revision #		01h,00h
166-253	Vendor specific		00h
254-255	Integrity CRC	W29N01HZ	B6h, 59h
		W29N01HW	B8h, E3h
256-511	Value of bytes 0-255		
512-767	Value of bytes 0-255		
>767	Additional redundant parameter pages		

x16 device : the ID is outputted at word units, and defined lower-byte (IO0-7). ID table shows only lower-byte ID.

Table 9.3 Parameter Page Output Value

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

9.1.5 READ STATUS (70h)

The W29N01HZ/W has an 8-bit Status Register which can be read during device operation. Refer to Table 9.4 for specific Status Register definitions. After writing 70h command to the Command Register, read cycles will only read from the Status Register. The status can be read from I/O[7:0] outputs, as long as #CE and #RE are LOW. Note; #RE does not need to be toggled for Status Register read. The Command Register remains in status read mode until another command is issued. To change to normal read mode, issue the PAGE READ (00h) command. After the PAGE READ command is issued, data output starts from the initial column address.




Figure 9-5 Read Status Operation

SR bit	Page Read	Page Program	Block Erase	Definition
I/O 0	Not Use	Pass/Fail	Pass/Fail	0=Successful Program/Erase 1=Error in Program/Erase
I/O 1	Not Use	Not Use	Not Use	0
I/O 2	Not Use	Not Use	Not Use	0
I/O 3	Not Use	Not Use	Not Use	0
I/O 4	Not Use	Not Use	Not Use	0
I/O 5	Ready/Busy	Ready/Busy	Ready/Busy	Ready = 1 Busy = 0
I/O 6	Ready/Busy	Ready/Busy	Ready/Busy	Ready = 1 Busy = 0
I/O 7	Write Protect	Write Protect	Write Protect	Unprotected = 1 Protected = 0

Table 9.4 Status Register Bit Definition

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

9.2 PROGRAM Operation

9.2.1 PAGE PROGRAM (80h-10h)

The W29N01HZ/W Page Program command will program pages sequentially within a block, from the lower order page address to higher order page address. Programming pages out of sequence is prohibited. The W29N01HZ/W supports partial-page programming operations up to 4 times before an erase is required if partitioning a page. Note; programming a single bit more than once without first erasing it is not supported.

9.2.2 SERIAL DATA INPUT (80h)

Page Program operation starts with the execution of the Serial Data Input command (80h) to the Command Register, following next by inputting four address cycles and then the data is loaded. Serial data is loaded to Data register with each #WE cycle. The Program command (10h) is written to the Command Register after the serial data input is finished. At this time the internal write state controller automatically executes the algorithms for program and verifies operations. Once the programming starts, determining the completion of the program process can be done by monitoring the RY/#BY output or the Status Register Bit 6, which will follow the RY/#BY signal. RY/#BY will stay LOW during the internal array programming operation during the period of (tPROG). During page program operation, only two commands are available, READ STATUS (70h) and RESET (FFh). When the device status goes to the ready state, Status Register Bit 0 (I/O0) indicates whether the program operation passed (Bit0=0) or failed (Bit0=1), (see Figure 9-6). The Command Register remains in read status mode until the next command is issued.




Figure 9-6 Page Program

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

9.2.3 RANDOM DATA INPUT (85h)

After the Page Program (80h) execution of the initial data has been loaded into the Data register, if the need for additional writing of data is required, using the RANDOM DATA INPUT (85h) command can perform this function to a new column address prior to the Program (10h) command. The RANDOM DATA INPUT command can be issued multiple times in the same page (See Figure 9-7).




Figure 9-7 Random Data Input

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

9.3 COPY BACK Operation

Copy Back operations require two command sets. Issue a READ for COPY BACK (00h-35h) command first, then the PROGRAM for COPY BACK (85h-10h) command.

9.3.1 READ for COPY BACK (00h-35h)

The READ for COPY BACK command is used together with the PROGRAM for COPY BACK (85h-10h) command. To start execution, READ for COPY BACK (00h) command is written to the Command Register, followed by the four cycles of the source page address. To start the transfer of the selected page data from the memory array to the Data register, write the 35h command to the Command Register.

After execution of the READ for COPY BACK command sequence and RY/#BY returns to HIGH marking the completion of the operation, the transferred data from the source page into the Data register may be read out by toggling #RE. Data is output sequentially from the column address that was originally specified with the READ for COPY BACK command. RANDOM DATA OUTPUT (05h-E0h) commands can be issued multiple times without any limitation after READ for COPY BACK command has been executed (see Figures 9-8 and 9-9).

At this point the device is in ready state to accept the PROGRAM for COPY BACK command.

9.3.2 PROGRAM for COPY BACK (85h-10h)

After the READ for COPY BACK command operation has been completed and RY/#BY goes HIGH, the PROGRAM for COPY BACK command can be written to the Command Register. The command results in the transfer of data to the Data Register, then internal operations start programming of the new destination page. The sequence would be, write 85h to the Command Register, followed by the four cycle destination page address to the NAND array. Next write the 10h command to the Command Register; this will signal the internal controller to automatically start to program the data to new destination page. During this programming time, RY/#BY will LOW. The READ STATUS command can be used instead of the RY/#BY signal to determine when the program is complete. When Status Register Bit 6 (I/O6) equals to “1”, Status Register Bit 0 (I/O0) will indicate if the operation was successful or not.

The RANDOM DATA INPUT (85h) command can be used during the PROGRAM for COPY BACK command for modifying the original data. Once the data is copied into the Data register using the READ for COPY BACK (00h-35h) command, follow by writing the RANDOM DATA INPUT (85h) command, along with the address of the data to be changed. The data to be changed is placed on the external data pins. This operation copies the data into the Data register. Once the 10h command is written to the Command Register, the original data and the modified data are transferred to the Data Register, and programming of the new page commences. The RANDOM DATA INPUT command can be issued numerous times without limitation, as necessary before starting the programming sequence with 10h command.

Since COPY BACK operations do not use external memory and the data of source page might include a bit errors, a competent ECC scheme should be developed to check the data before programming data to a new destination page.

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com




Figure 9-8 Copy Back Program Operation




Figure 9-9 Copy Back Operation with Random Data Input

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

9.4 BLOCK ERASE Operation

9.4.1 BLOCK ERASE (60h-D0h)

Erase operations happen at the architectural block unit. This W29N01HZ/W has 1024 erase blocks. Each block is organized into 64 pages (x8:2112 bytes/page, x16:1056 words/page), 132K bytes (x8:128K + 4K bytes, x16:64 K+ 2Kwords)/block. The BLOCK ERASE command operates on a block by block basis.

Erase Setup command (60h) is written to the Command Register. Next, the two cycle block address is written to the device. The page address bits are loaded during row address cycle, but are ignored. The Erase Confirm command (D0h) is written to the Command Register at the rising edge of #WE, RY/#BY goes LOW and the internal controller automatically handles the block erase sequence of operation. RY/#BY goes LOW during Block Erase internal operations for a period of tBERS,

The READ STATUS (70h) command can be used for confirm block erase status. When Status Register Bit6 (I/O6) becomes to “1”, block erase operation is finished. Status Register Bit0 (I/O0) will indicate a pass/fail condition (see Figure 9-10).




Figure 9-10 Block Erase Operation

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

9.5 RESET Operation

9.5.1 RESET (FFh)

READ, PROGRAM, and ERASE commands can be aborted by the RESET (FFh) command during the time the W29N01HZ/W is in the busy state. The Reset operation puts the device into known status. The data that is processed in either the programming or erasing operations are no longer valid. This means the data can be partially programmed or erased and therefore data is invalid. The Command Register is cleared and is ready to accept next command. The Data Register contents are marked invalid.

The Status Register indicates a value of E0h when #WP is HIGH; otherwise a value of 60h is written when #WP is LOW. After RESET command is written to the command register, RY/#BY goes LOW for a period of tRST (see Figure 9-11).




Figure 9-11 Reset Operation

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

9.6 WRITE PROTECT

#WP pin can enable or disable program and erase commands preventing or allowing program and erase operations. Figure 9-12 to 9-17 shows the enabling or disabling timing with #WP setup time (tWW) that is from rising or falling edge of #WP to latch the first commands. After first command is latched, #WP pin must not toggle until the command operation is complete and the device is in the ready state. (Status Register Bit5 (I/O5) equal 1)




Figure 9-12 Erase Enable




Figure 9-13 Erase Disable




Figure 9-14 Program Enable

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com




Figure 9-15 Program Disable




Figure 9-16 Program for Copy Back Enable




Figure 9-17 Program for Copy Back Disable

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

10. ELECTRICAL CHARACTERISTICS

10.1 Absolute Maximum Ratings (1.8V)

PARAMETERS	SYMBOL	CONDITIONS	RANGE	UNIT
Supply Voltage	VCC		–0.6 to +2.4	V
Voltage Applied to Any Pin	VIN	Relative to Ground	–0.6 to +2.4	V
Storage Temperature	TSTG		–65 to +150	°C
Short circuit output current, I/Os			5	mA

Table 10.1 Absolute Maximum Ratings

Notes:

1. **Minimum DC voltage is -0.6V on input/output pins. During transitions, this level may undershoot to -2.0V for periods <30ns.**
2. **Maximum DC voltage on input/output pins is Vcc+0.3V which, during transitions, may overshoot to Vcc+2.0V for periods <20ns.**
3. **This device has been designed and tested for the specified operation ranges. Proper operation outside of these levels is not guaranteed. Exposure to absolute maximum ratings may affect device reliability. Exposure beyond absolute maximum ratings may cause permanent damage.**

10.2 Operating Ranges (1.8V)

PARAMETER	SYMBOL	CONDITIONS	SPEC		UNIT
			MIN	MAX	
Supply Voltage	VCC		1.7	1.95	V
Ambient Temperature, Operating	TA	Industrial	-40	+85	°C
		Industrial Plus	-40	+105	

Table 10.2 Operating Ranges

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

10.3 Device Power-up Timing

The device is designed to avoid unexpected program/erase operations during power transitions. When the device is powered on, an internal voltage detector disables all functions whenever Vcc is below about 2V at 3V device, 1.1V at 1.8V device.. Write Protect (#WP) pin provides hardware protection and is recommended to be kept at VIL during power up and power down. A recovery time of minimum 1ms is required before internal circuit gets ready for any command sequences (See Figure 10-1).




Figure 10-1 Power ON/OFF sequence

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

10.4 DC Electrical Characteristics

PARAMETER	SYMBOL	CONDITIONS	SPEC			UNIT
			MIN	TYP	MAX	

Sequential Read current	Icc1	tRC= tRC MIN
		#CE=VIL
		IOUT=0mA
			-	13	25	mA

Program current	Icc2	-	-	10	25	mA
Erase current	Icc3	-	-	10	25	mA
Standby current (TTL)	ISB1	#CE=VIH #WP=0V/Vcc	-	-	1	mA
Standby current (CMOS) Industrial	ISB2	#CE=Vcc – 0.2V #WP=0V/Vcc	-	10	50	µA
Standby current (CMOS) Industrial Plus			-	10	100	µA
Input leakage current	ILI	VIN= 0 V to Vcc	-	-	±10	µA
Output leakage current	ILO	VOUT=0V to Vcc	-	-	±10	µA
Input high voltage	VIH	I/O15~0, #CE,#WE,#RE, #WP,CLE,ALE	0.8 x Vcc	-	Vcc + 0.3	V
Input low voltage	VIL	-	-0.3	-	0.2 x Vcc	V
Output high voltage(1)	VOH	IOH=-100µA	Vcc -0.1	-	-	V
Output low voltage(1)	VOL	IOL=+100µA	-	-	0.1	V
Output low current	IOL(RY/#BY)	VOL=0.2V	3	4		mA

Table 10.3 DC Electrical Characteristics

Note:

1. **VOH and VOL may need to be relaxed if I/O drive strength is not set to full.**

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

10.6 AC Measurement Conditions

PARAMETER	SYMBOL	SPEC		UNIT
		MIN	MAX	
Input Capacitance(1), (2)	C_{IN}	-	10	pF
Input/Output Capacitance(1), (2)	C_{IO}	-	10	pF
Input Rise and Fall Times	TR/TF	-	2.5	ns
Input Pulse Voltages	-	0 to VCC		V
Input/Output timing Voltage	-	Vcc/2		V
Output load (1)	CL	1TTL GATE and CL=30pF		-

Table 10.4 AC Measurement Conditions

Notes:

1. **Verified on device characterization , not 100% tested**
2. **Test conditions TA=25'C, f=1MHz, VIN=0V**

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

10.7 AC Timing Characteristics for Command, Address and Data Input (1.8V)

PARAMETER	SYMBOL	SPEC		UNIT
		MIN	MAX	
ALE to Data Loading Time(1)	tADL	70	-	ns
ALE Hold Time	tALH	5	-	ns
ALE setup Time	tALS	10	-	ns
#CE Hold Time	tCH	5	-	ns
CLE Hold Time	tCLH	5	-	ns
CLE setup Time	tCLS	10	-	ns
#CE setup Time	tCS	20	-	ns
Data Hold Time	tDH	5	-	ns
Data setup Time	tDS	10	-	ns
Write Cycle Time	tWC	25	-	ns
#WE High Hold Time	tWH	10	-	ns
#WE Pulse Width	tWP	12	-	ns
#WP setup Time	tWW	100	-	ns

Table 10.5 AC Timing Characteristics for Command, Address and Data Input

Note:

1. **tADL is the time from the #WE rising edge of final address cycle to the #WE rising edge of first data cycle.**

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

10.8 AC Timing Characteristics for Operation (1.8V)

PARAMETER	SYMBOL	SPEC		UNIT
		MIN	MAX	
ALE to #RE Delay	tAR	10	-	ns
#CE Access Time	tCEA	-	25	ns
#CE HIGH to Output High-Z(1)	tCHZ	-	50	ns
CLE to #RE Delay	tCLR	10	-	ns
#CE HIGH to Output Hold	tCOH	15	-	ns
Output High-Z to #RE LOW	tIR	0	-	ns
Data Transfer from Cell to Data Register	tR	-	25	µs
READ Cycle Time	tRC	25	-	ns
#RE Access Time	tREA	-	22	ns
#RE HIGH Hold Time	tREH	10	-	ns
#RE HIGH to Output Hold	tRHOH	15	-	ns
#RE HIGH to #WE LOW	tRHW	100	-	ns
#RE HIGH to Output High-Z(1)	tRHZ	-	100	ns
#RE LOW to output hold	tRLOH	3	-	ns
#RE Pulse Width	tRP	12	-	ns
Ready to #RE LOW	tRR	20	-	ns
Reset Time (READ/PROGRAM/ERASE)(2)	tRST	-	5/10/500	µs
#WE HIGH to Busy(3)	tWB	-	100	ns
#WE HIGH to #RE LOW	tWHR	80	-	ns

Table 10.6 AC Timing Characteristics for Operation

Notes:

1. **Transition is measured ±200mV from steady-state voltage with load. This parameter is sampled and not 100 % tested**
2. **The RESET (FFh) command is issued while the device is idle, the device goes busy for a maximum of 5us.**
3. **Do not issue new command during tWB, even if RY/#BY is ready.**

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

10.9 Program and Erase Characteristics

PARAMETER	SYMBOL	SPEC		UNIT
		TYP	MAX	
Number of partial page programs	NoP	-	4	cycles
Page Program time	tPROG	250	700	µs
Block Erase Time	tBERS	2	10	ms

Table 10.7 Program and Erase Characteristics

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

11. TIMING DIAGRAMS




Figure 11-1 Command Latch Cycle





Figure 11-2 Address Latch Cycle

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com



Note: 1. Din Final = 2,111(x8)

Figure 11-3 Data Latch Cycle




Figure 11-4 Serial Access Cycle after Read

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com




Figure 11-5 Serial Access Cycle after Read (EDO)




Figure 11-6 Read Status Operation

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com




Figure 11-7 Page Read Operation




Figure 11-8 #CE Don't Care Read Operation

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com





Figure 11-9 Random Data Output Operation

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com



Note: 1. See Table 9.1 for actual value.

Figure 11-10 Read ID




Figure 11-11 Page Program

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com




Figure 11-12 #CE Don't Care Page Program Operation




Figure 11-13 Page Program with Random Data Input

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com




Figure 11-14 Copy Back




Figure 11-15 Block Erase

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com




Figure 11-16 Reset

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

12. INVALID BLOCK MANAGEMENT

12.1 Invalid Blocks

The W29N01HZ/W may have initial invalid blocks when it ships from factory. Also, additional invalid blocks may develop during the use of the device. Nvb represents the minimum number of valid blocks in the total number of available blocks (See Table 12.1). An invalid block is defined as blocks that contain one or more bad bits. Block 0, block address 00h is guaranteed to be a valid block at the time of shipment.

Parameter	Symbol	Min	Max	Unit
Valid block number	Nvb	1004	1024	blocks

Table 12.1 Valid Block Number

12.2 Initial Invalid Blocks

Initial invalid blocks are defined as blocks that contain one or more invalid bits when shipped from factory.

Although the device contains initial invalid blocks, a valid block of the device is of the same quality and reliability as all valid blocks in the device with reference to AC and DC specifications. The W29N01HZ/W has internal circuits to isolate each block from other blocks and therefore, the invalid blocks will not affect the performance of the entire device.

Before the device is shipped from the factory, it will be erased and invalid blocks are marked. All initial invalid blocks are marked with non-FFh at the first byte of spare area on the 1st or 2nd page. The initial invalid block information cannot be recovered if inadvertently erased. Therefore, software should be created to initially check for invalid blocks by reading the marked locations before performing any program or erase operation, and create a table of initial invalid blocks as following flow chart

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com




Figure 12-1 Flow Chart of Create Initial Invalid Block Table

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

12.3 Error in Operation

Additional invalid blocks may develop in the device during its life cycle. Following the procedures herein is required to guarantee reliable data in the device.

After each program and erase operation, check the status read to determine if the operation failed. In case of failure, a block replacement should be done with a bad-block management algorithm. The system has to use a minimum 4-bit ECC per 528 bytes of data to ensure data recovery.

Operation	Detection and recommended procedure
Erase	Status read after erase → Block Replacement
Program	Status read after program → Block Replacement
Read	Verify ECC → ECC correction

Table 12.2 Block Failure




Figure 12-2 Bad Block Replacement

Note:

1. **An error happens in the nth page of block A during program or erase operation.**
2. **Copy the data in block A to the same location of block B which is valid block.**
3. **Copy the nth page data of block A in the buffer memory to the nth page of block B**
4. **Creating or updating bad block table for preventing further program or erase to block A**

.


12.4 Addressing in Program Operation

The pages within the block have to be programmed sequentially from LSB (least significant bit) page to the MSB (most significant bit) within the block. The LSB is defined as the start page to program, does not need to be page 0 in the block. Random page programming is prohibited.

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

13. PACKAGE DIMENSIONS

13.1 TSOP 48-pin 12x20




Symbol	MILLIMETER			INCH		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	—	—	1.20	—	—	0.047
A1	0.05	—	—	0.002	—	—
A2	0.95	1.00	1.05	0.037	0.039	0.041
D	18.3	18.4	18.5	0.720	0.724	0.728
H_D	19.8	20.0	20.2	0.780	0.787	0.795
E	11.9	12.0	12.1	0.468	0.472	0.476
b	0.17	0.22	0.27	0.007	0.009	0.011
c	0.10	—	0.21	0.004	—	0.008
e	—	0.50	—	—	0.020	—
L	0.50	0.60	0.70	0.020	0.024	0.028
L1	—	0.80	—	—	0.031	—
Y	—	—	0.10	—	—	0.004
θ	0	—	5	0	—	5

Figure 13-1 TSOP 48-pin 12x20mm

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

13.2 Fine-Pitch Ball Grid Array 48-ball




SYMBOL	DIMENSION (MM)		
	MIN.	NOM.	MAX.
A	0.86	0.93	1.00
A1	0.25	---	0.40
b	0.40	0.45	0.50
D	6.40	6.50	6.60
E	7.90	8.00	8.10
D1	4.00 BSC		
E1	5.60 BSC.		
eD	0.80 BSC.		
eE	0.80 BSC.		
aaa	0.15		
bbb	--	--	0.10
ccc	--	--	0.10
ddd	--	--	0.15

Figure 13-2 Fine-Pitch Ball Grid Array 48-Ball

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

13.3 Fine-Pitch Ball Grid Array 63-ball



SYMBOL	DIMENSION (MM)		
	MIN.	NOM.	MAX.
A	---	---	1.00
A1	0.25	---	0.40
b	0.40	0.45	0.50
D	8.90	9.00	9.10
E	10.90	11.00	11.10
D1	7.20 BSC		
E1	8.80 BSC.		
eD	0.80 BSC.		
eE	0.80 BSC.		
aaa	0.15		
bbb	--	--	0.10
ccc	--	--	0.10
ddd	--	--	0.20
N	63		

Note:
1. Ball land:0.5mm, Ball opening:0.4mm,
   PCB Ball land suggested 0.4mm

Figure 13-3 Fine-Pitch Ball Grid Array 63-Ball (9x11mm)

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

14. ORDERING INFORMATION




Figure 14-1 Ordering Part Number Description

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

15. VALID PART NUMBERS

The following table provides the valid part numbers for the W29N01HZ/W NAND Flash Memory. Please contact Winbond for specific availability by density and package type. Winbond NAND Flash memories use a 12-digit Product Number for ordering.

Part Numbers for Industrial Temperature:

PACKAGE TYPE	DENSITY	VCC	BUS	PRODUCT NUMBER	TOP SIDE MARKING
S TSOP-48	1G-bit	1.8V	X8	W29N01HZSINF	W29N01HZSINF
S TSOP-48	1G-bit	1.8V	X16	W29N01HWSINF	W29N01HWSINF
D VFBGA-48	1G-bit	1.8V	X8	W29N01HZDINF	W29N01HZDINF
D VFBGA-48	1G-bit	1.8V	X16	W29N01HWDINF	W29N01HWDINF
B VFBGA-63	1G-bit	1.8V	X8	W29N01HZBINF	W29N01HZBINF
B VFBGA-63	1G-bit	1.8V	X16	W29N01HWBINF	W29N01HWBINF

Table 15.1 Part Numbers for Industrial Temperature

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

Part Numbers for Industrial Plus Temperature:

PACKAGE TYPE	DENSITY	VCC	BUS	PRODUCT NUMBER	TOP SIDE MARKING
S TSOP-48	1G-bit	1.8V	X8	W29N01HZSJNF	W29N01HZSJNF
S TSOP-48	1G-bit	1.8V	X16	W29N01HWSJNF	W29N01HWSJNF
D VFBGA-48	1G-bit	1.8V	X8	W29N01HZDJNF	W29N01HZDJNF
D VFBGA-48	1G-bit	1.8V	X16	W29N01HWDJNF	W29N01HWDJNF
B VFBGA-63	1G-bit	1.8V	X8	W29N01HZBJNF	W29N01HZBJNF
B VFBGA-63	1G-bit	1.8V	X16	W29N01HWBJNF	W29N01HWBJNF

Table 15.2 Part Numbers for Industrial Plus Temperature

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

16. REVISION HISTORY

VERSION	DATE	PAGE	DESCRIPTION
0.1	9/26/2015	-	New Create
A	11/20/2015	-	Remove “Preliminary”
B	2/1/2016	19, 32	Update Parameter Page Output Value Update Icc1, Icc2, Icc3 maximum value
C	3/30/2016	7, 50, 53, 54	Add TSOP-48 package
D	12/1/2017	6 9, 11, 56 12	Add description of TSOP-48 package Add X16 pin assignment and valid part numbers Change description of DNU
E	1/11/2018	53	Update Package Dimension of VFBGA-48
F	10/31/2019	6, 33, 55, 57	Add Industrial Plus Grade
G	3/30/2020	6, 38 23 35	Changed tRC (min) from 25ns to 35ns Added CRC values Added ISB2 for Industrial Plus Grade
H	11/4/2020	6, 38	Changed tRC (min) from 35ns to 25ns

Table 16.1 History Table

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com

Trademarks

Winbond is trademark of *Winbond Electronics Corporation.*
All other marks are the property of their respective owner.

Important Notice

Winbond products are not designed, intended, authorized or warranted for use as components in systems or equipment intended for surgical implantation, atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, or for other applications intended to support or sustain life. Furthermore, Winbond products are not intended for applications wherein failure of Winbond products could result or lead to a situation where in personal injury, death or severe property or environmental damage could occur.

Winbond customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Winbond for any damages resulting from such improper use or sales.

Please note that all data and specifications are subject to change without notice.
All the trademarks of products and companies mentioned in this datasheet belong to their respective owners.

深圳市满度科技有限公司
Web:www.manduic.com
Tel:150-1290-5940
Email:sales@manduic.com